

Basic Temperature and Limit Controller Solutions at Our Most Economical Price

Watlow's basic and limit microprocessor based controllers provide an economical solution for applications requiring simple on-off control. These controllers and limits are available in a broad range of packaging options, allowing users to select the best version for their individual application. The controllers and limits are available with or without an operator interface and can be ordered in square 1/8th DIN panel mount, DIN-rail mount or open board design configurations.

The basic and limit design provides significant improvements in the performance and repeatability and accuracy offered by analog basic temperature and limit controllers.

The variable options, SERIES CV (controller) and SERIES LV (limit), include an operator interface for viewing and selecting the set point. A red, four-character seven segment LED displays the set point with a push to show process option. The set point selection is made with a continuous turn rotary encoder, or with discrete up/down cursor keys. Operating range temperature values are customer definable in the product configuration part number.

The fixed options, SERIES CF (controller) and SERIES LF (limit), offer fixed set points and are supplied without an operator interface. Operating set point temperature values are customer definable in the product configuration part number. The SERIES TM-temperature indicator is available as an additional order option.

These basic and limit controllers are UL[®] recognized and include CE approvals. The limit controllers are FM approved with special UL[®] approval for the open board potted versions. CV and LV panel mount controllers ordered with discrete up/down cursor keys include NEMA 4X/IP65 seal protection. Watlow's basic temperature and limit controllers include industry leading service and support and are backed by a three-year warranty.

Applications

- Food preparation
- Industrial machinery
- Packaging
- Plastics processing

UL[®] is a registered trademark of Underwriter's Laboratories, Inc.



Features and Benefits

Fixed or adjustable set points

- Provide tamper-proof operation
- Offer control flexibility

Four character LED display

- Improves set point selection accuracy

Multiple mounting options

- Minimize installation time

Heat or cool operation

- Provides application flexibility

High or low limit with auto or manual reset

- Provides application flexibility

Fahrenheit or celsius operation with indication

- Offers application flexibility

Sensor break protection

- Provides positive system shutdown

Agency approvals

- Meet certification requirements/compliance

Microprocessor based technology

- Ensures accurate repeatable control



1241 Bundy Boulevard, P.O. Box 5580
Winona, Minnesota 55987-5580 USA
Phone: +1 (507) 454-5300
Fax: +1 (507) 452-4507
Internet: www.watlow.com
e-mail: info@watlow.com

WIN-BTLC-0606

ISO 9001



Specifications

On-off Controller

- Microprocessor based, on-off control mode
- Nominal switching hysteresis, typically 1.7°C (3°F)
- Input filter time: 1 second

Limit Controller

- Microprocessor based, limit controller
- Nominal switching hysteresis, typically 1.7°C (3°F)
- High or low limit, factory selectable
- Latching output requires manual reset upon over or under temperature condition
- Manual or automatic reset on power loss, factory selectable
- Internal front panel or external customer supplied momentary reset switch
- Input filter time: 1 second

Operator Interface

- Four digit, seven segment LED displays, 7 mm (0.28 in.) high
- °F or °C indicator LED
- Load/Alarm indicator LED
- Continuous turn, velocity sensitive rotary encoder for set point adjustment
- Front panel key on push for set point or push for show process options (on-off controller only)
- Front panel SET/RESET key on variable set point models (limit controller only)
- No operator interface on fixed set point models

Standard Conditions For Specifications

- Rated line voltage, 50 to 60Hz, 0 to 90 percent RH non-condensing, 15-minute warm-up
- Calibration ambient range: 25°C (77°F) ±3°C

Sensor Input

Thermocouple

- Grounded or ungrounded
- Type E, J, K, T thermocouple types
- >10 MΩ input impedance
- 250 nV input referenced error per 1Ω source resistance

RTD

- 2-wire platinum, 100Ω
- DIN curve (0.00385 curve)
- 125 μA nominal RTD excitation current

Input Accuracy Span Range

Type E:	-200 to 800°C	or	-328 to 1470°F
Type J:	0 to 750°C	or	32 to 1382°F
Type K:	-200 to 1250°C	or	-328 to 2282°F
Type T:	-200 to 350°C	or	-328 to 662°F
RTD (DIN)	-200 to 800°C	or	-328 to 1472°F

Thermocouple Input

- Calibration accuracy: ±1 percent of input accuracy span, ±1° at standard conditions and actual calibration ambient
Exception: Type T, ±2.4 percent of input accuracy span for -200 to 0°C (-328 to 32°F)
- Temperature stability: ±0.3 degree per degree change in ambient

RTD Input

- Calibration accuracy ±1 percent of input accuracy span ±1° at standard conditions and actual calibration ambient
- Temperature stability: ±0.2 degree per degree change in ambient

Allowable Operating Ranges

Type E:	-200 to 800°C	or	-328 to 1470°F
Type J:	-210 to 1038°C	or	-346 to 1900°F
Type K:	-270 to 1370°C	or	-454 to 2500°F
Type T:	-270 to 400°C	or	-454 to 750°F
RTD (DIN)	-200 to 800°C	or	-328 to 1472°F

Output Types

Switched dc (non-isolated, on-off controller only)

- Supply voltage maximum: 24V=(dc) into an infinite load
- Supply voltage minimum: 5V=(dc) at 10mA
- Minimum load impedance: 500Ω

Electromechanical Relay, Form C

- Minimum load current: 100mA
- 8 A @ 240V~(ac) or 30V=(dc) maximum, resistive
- 250VA pilot duty, 120/240V~(ac) maximum, inductive
- Use RC suppression for inductive loads
- Electrical life 100,000 cycles at rated current

External Reset Switch (limit controller only)

- Momentary, dry contact closure

Agency Approvals (on-off controller only)

- UL® 873 Recognized Temperature Controller and Indicator, File # E43684
- UL® 197 Reviewed for use in food service appliances
- ANSI Z21.23 Gas Appliance Thermostat approval
- Temperature Control and Indicator CSA 22.2 No. 24, File # 30586
- CE^①
- NEMA 4X/IP65 (SERIES CV and LV panel mount controllers with up/down cursor keys)

Agency Approvals (limit controller only)

SERIES LF (potted version only)

- UL® 991 recognized temperature limit for food service industry

SERIES LV and SERIES LF (including potted version)

- UL® 873 recognized temperature regulator, File # E43684
- UL® 197 reviewed for use in food service appliances
- ANSI Z21.23 Gas appliance thermostat approval
- CSA C22.2#24 approved temperature control, File # 30586
- FM Class 3545 temperature limit switches, File # 3017239
- CE^①

Terminals

- 6.3 mm (0.25 in.) quick connect, push on terminal or removable screw style terminal block

Power

- 24V~(ac) +10 percent; -15 percent; 50/60Hz, ±5 percent
- 120V~(ac) +10 percent; -15 percent; 50/60Hz, ±5 percent
- 230 to 240V~(ac) +10 percent; -15 percent; 50/60Hz, ±5 percent
- 187 to 264V~(ac) SERIES LF and CF only
- 10VA maximum power consumption
- Data retention upon power failure via nonvolatile memory

Operating Environment

- 0 to 70°C (32 to 158°F)
- 0 to 90 percent RH, non-condensing
- Storage temperature: -40 to 85°C (-40 to 185°F)

Dimensions

- DIN-rail model can be DIN-rail or chassis mount
DIN-rail spec DIN 50022, 35 mm x 7.5 mm (1.38 in. x 0.30 in.)

Style	Width	Height	Depth
Open Board	61.7 mm (2.43 in.)	61.7 mm (2.43 in.)	45.1 mm (1.78 in.)
Potted	70.1 mm (2.76 in.)	102.9 mm (4.05 in.)	46.6 mm (1.84 in.)
DIN-Rail	78.1 mm (3.08 in.)	112.3 mm (4.42 in.)	90.7 mm (3.57 in.)
Square ¼ DIN Panel	72.4 mm (2.85 in.)	72.4 mm (2.85 in.)	Behind panel 51.7 mm (2.04 in.)

^①See declaration of conformity.

Ordering Information

T M A A A A A A A A

Indicator only, four character, seven segment display

Power Supply

B = 120V~(ac)
D = 230 to 240V~(ac)
F = 24V~(ac)

Package

1 = Panel mount, 1/8" DIN square - spade terminals
2 = DIN-rail mount - spade terminals
5 = Panel mount, 1/8" DIN square - screw terminals
6 = DIN-rail mount - screw terminals
A = NEMA 4X panel mount, (spade terminals)
C = NEMA 4X panel mount, (screw terminals)

Sensor Type and Scale

H = T/C Type J °F (-346 to 1900°F)
J = T/C Type J °C (-210 to 1038°C)
K = T/C Type K °F (-454 to 2500°F)
L = T/C Type K °C (-270 to 1370°C)
M = T/C Type T °F (-454 to 750°F)
N = T/C Type T °C (-270 to 400°C)
P = RTD °F (-328 to 1472°F)
R = RTD °C (-200 to 800°C)
S = T/C Type E °F (-328 to 1470°F)
T = T/C Type E °C (-200 to 800°C)

Overlay/Customs Options

A = Standard with Watlow logo
1 = Standard without Watlow logo

Ordering Information

L V

Limit control with eight amp relay output. Rotary set point, adjustment, four character, seven segment display, reset switch

Power Supply

C = 120V~(ac)
E = 230 to 240V~(ac)
G = 24V~(ac)

Package

1 = Panel mount, 1/8" DIN square - spade terminals
2 = DIN-rail mount - spade terminals
5 = Panel mount, 1/8" DIN square - screw terminals
6 = DIN-rail mount - screw terminals
A = NEMA 4X panel mount, tactile keys (spade terminals)
B = DIN-rail mount, tactile keys (spade terminals)
C = NEMA 4X panel mount, tactile keys (screw terminals)
D = DIN-rail mount, tactile keys (screw terminals)

Sensor Type and Scale

H = T/C Type J °F (-346 to 1900°F)
J = T/C Type J °C (-210 to 1038°C)
K = T/C Type K °F (-454 to 2500°F)
L = T/C Type K °C (-270 to 1370°C)
M = T/C Type T °F (-454 to 750°F)
N = T/C Type T °C (-270 to 400°C)
P = RTD °F (-328 to 1472°F)
R = RTD °C (-200 to 800°C)
S = T/C Type E °F (-328 to 1470°F)
T = T/C Type E °C (-200 to 800°C)

Limit Type

U = High limit manual reset
W = High limit auto reset
Y = Low limit manual reset
Z = Low limit auto reset

Low Set Point Operating Range Value[ⓐ]

High Set Point Operating Range Value[ⓐ]

Overlay/Customs Options

A = Standard with Watlow logo
1 = Standard without Watlow logo

[ⓐ]A (-) is used in the left most digit of the fixed set point indicates a negative temperature value

Ordering Information

L F A A A A

Limit control with eight amp relay output. Fixed set point, no user interface

Power Supply

C = 120V~(ac)
E = 230 to 240V~(ac)
G = 24V~(ac)

Package

1 = Panel mount, 1/8" DIN square - spade terminals
2 = DIN-rail mount - spade terminals
3 = Open, non potted - spade terminals
4 = Potted case - spade terminals
5 = Panel mount, 1/8" DIN square - screw terminals
6 = DIN-rail mount - screw terminals
7 = Open, non potted - screw terminals

Sensor Type and Scale

H = T/C Type J °F (-346 to 1900°F)
J = T/C Type J °C (-210 to 1038°C)
K = T/C Type K °F (-454 to 2500°F)
L = T/C Type K °C (-270 to 1370°C)
M = T/C Type T °F (-454 to 750°F)
N = T/C Type T °C (-270 to 400°C)
P = RTD °F (-328 to 1472°F)
R = RTD °C (-200 to 800°C)
S = T/C Type E °F (-328 to 1470°F)
T = T/C Type E °C (-200 to 800°C)

Limit Type

U = High limit manual reset
W = High limit auto reset
Y = Low limit manual reset
Z = Low limit auto reset

Fixed Set Point Temperature Value[ⓐ]

Overlay/Customs Options

A = Standard with Watlow logo
1 = Standard without Watlow logo

[ⓐ]A (-) is used in the left most digit of the fixed set point indicates a negative temperature value

Your Authorized Watlow Distributor is:

Ordering Information

C F A A A A

On-off controller, fixed set point, no user interface

Power Supply

- B = 120V~(ac), switched dc output
- C = 120V~(ac), eight amp relay output
- D = 230 to 240V~(ac), switched dc output
- E = 230 to 240V~(ac), eight amp relay output
- F = 24V~(ac), switched dc output
- G = 24V~(ac), eight amp relay output

Package

- 1 = Panel mount, 1/8th DIN square - spade terminals
- 2 = DIN-rail mount - spade terminals
- 3 = Open board, non potted - spade terminals
- 4 = Potted case - spade terminals
- 5 = Panel mount, 1/8th DIN square - screw terminals
- 6 = DIN-rail mount - screw terminals
- 7 = Open board, non potted - screw terminals

Sensor Type and Scale

- H = T/C Type J °F (-346 to 1900°F)
- J = T/C Type J °C (-210 to 1038°C)
- K = T/C Type K °F (-454 to 2500°F)
- L = T/C Type K °C (-270 to 1370°C)
- M = T/C Type T °F (-454 to 750°F)
- N = T/C Type T °C (-270 to 400°C)
- P = RTD °F (-328 to 1472°F)
- R = RTD °C (-200 to 800°C)
- S = T/C Type E °F (-328 to 1470°F)
- T = T/C Type E °C (-200 to 800°C)

Control Type

- H = Heat
- C = Cool

Fixed Set Point Temperature Value[ⓐ]

Overlay/Customs Options

- A = Standard with Watlow logo
- 1 = Standard without Watlow logo

[ⓐ]A (-) is used in the left most digit of the fixed set point indicates a negative temperature value

Ordering Information

C V

On-off controller rotary set point adjustment, four character, seven segment display

Power Supply

- B = 120V~(ac), switched dc output
- C = 120V~(ac), eight amp relay output
- D = 230 to 240V~(ac), switched dc output
- E = 230 to 240V~(ac), eight amp relay output
- F = 24V~(ac), switched dc output
- G = 24V~(ac), eight amp relay output

Package

- 1 = Panel mount, 1/8th DIN square - spade terminals
- 2 = DIN-rail mount - spade terminals
- 5 = Panel mount, 1/8th DIN square - screw terminals
- 6 = DIN-rail mount - screw terminals
- A = NEMA 4X panel mount, tactile keys (spade terminals)
- B = DIN-rail mount, tactile keys (spade terminals)
- C = NEMA 4X panel mount, tactile keys (screw terminals)
- D = DIN-rail mount, tactile keys (screw terminals)

Sensor Type and Scale

- H = T/C Type J °F (-346 to 1900°F)
- J = T/C Type J °C (-210 to 1038°C)
- K = T/C Type K °F (-454 to 2500°F)
- L = T/C Type K °C (-270 to 1370°C)
- M = T/C Type T °F (-454 to 750°F)
- N = T/C Type T °C (-270 to 400°C)
- P = RTD °F (-328 to 1472°F)
- R = RTD °C (-200 to 800°C)
- S = T/C Type E °F (-328 to 1470°F)
- T = T/C Type E °C (-200 to 800°C)

Control Type

- H = Heat
- C = Cool

Low Set Point Operating Range Value[ⓐ]

High Set Point Operating Range Value[ⓐ]

Overlay/Customs Options

- A = Standard with Watlow logo
- B = Push to show process with Watlow logo
- C = Push to adjust set point with Watlow logo
- D = Show process push to adjust set point with Watlow logo
- 1 = Standard without Watlow logo
- 2 = Push to show process without Watlow logo
- 3 = Push to adjust set point without Watlow logo
- 4 = Show process push to adjust set point without Watlow logo

[ⓐ]A (-) is used in the left most digit of the fixed set point indicates a negative temperature value

To be automatically connected to the nearest North American Technical and Sales Office call:

1-800-WATLOW2

International Technical and Sales Offices: Australia, +61-3-9335-6449 • China, +86-21-3950-9510 • France, +33 (01) 3073-2425 • Germany, +49 (0) 7253-9400-0 • Italy, +39 (02) 458-8841 • Japan, +81-3-3518-6630 • Korea, +82-2-575-9804 • Malaysia, +60-3-7980-7741 • Mexico +52 (442) 217-6235 • Singapore, +65-6777-1266 • Spain, +34 916 751 292 • Sweden, +46 35-27-11-66 • Taiwan, +886-7-288-5168 • United Kingdom, +44 (0) 115-964-0777